

# Extra Flexible Single & Multiconductor PVC & Polyurethane Insulated Cables, *continued*

Number of Conductors	SINGLE CONDUCTOR DATA				Nominal Diameter Over Cabled Conductor	SHIELD		JACKET	
	Equivalent AWG	Strand Construction	Nominal Wall Thickness	Nominal Diameter		AWG of Shield	Nominal Diameter Over Shield	Nominal Wall Thickness	Nominal OD
2	28	19/40	.010	.035	.069	40	.083	.010	.103
2	26	26/40	.010	.038	.074	40	.088	.010	.108
2	26	66/44	.010	.039	.076	40	.090	.010	.110
2	26	19/38	.010	.039	.076	40	.090	.010	.110
2	24	3x35/44	.010	.045	.088	40	.102	.010	.122
2	24	42/40	.010	.043	.084	40	.098	.010	.118
2	24	19/36	.010	.044	.086	40	.100	.010	.120
2	23	3x50/44	.010	.050	.098	36	.121	.010	.141
2	22	66/40	.010	.049	.096	36	.119	.010	.139
2	22	26/36	.010	.049	.096	36	.119	.010	.139
2	20	7x37/44	.010	.060	.118	36	.141	.010	.161
2	20	7x15/40	.010	.059	.116	36	.139	.010	.159
2	20	42/36	.010	.057	.112	36	.135	.010	.155
2	18	7x59/44	.010	.070	.137	36	.160	.010	.180
2	18	7x24/40	.010	.070	.137	36	.160	.010	.180
3	34	16/46	.010	.027	.058	44	.067	.010	.087
3	34	10/44	.010	.027	.058	44	.067	.010	.087
3	34	5/40	.010	.028	.060	44	.069	.010	.089
3	32	26/46	.010	.029	.062	44	.071	.010	.091
3	32	16/44	.010	.029	.062	44	.071	.010	.091
3	32	7/40	.010	.029	.062	44	.071	.010	.091
3	30	41/46	.010	.032	.069	44	.078	.010	.098
3	30	25/44	.010	.032	.069	44	.078	.010	.098
3	30	7/38	.010	.032	.069	44	.078	.010	.098
3	29	52/46	.010	.033	.071	40	.085	.010	.105
3	28	65/46	.010	.035	.075	40	.089	.010	.109
3	28	40/44	.010	.035	.075	40	.089	.010	.109
3	28	19/40	.010	.035	.075	40	.089	.010	.109
3	26	26/40	.010	.038	.082	40	.096	.010	.116
3	26	66/44	.010	.039	.084	40	.098	.010	.118
3	26	19/38	.010	.039	.084	40	.098	.010	.118
3	24	3x35/44	.010	.045	.097	36	.120	.010	.140
3	24	42/40	.010	.043	.092	36	.115	.010	.135
3	24	19/36	.010	.044	.095	36	.118	.010	.138
3	23	3x50/44	.010	.050	.108	36	.131	.010	.151
3	22	66/40	.010	.049	.105	36	.128	.010	.148
3	22	26/36	.010	.049	.105	36	.128	.010	.148
3	20	7x37/44	.010	.060	.129	36	.152	.010	.172
3	20	7x15/40	.010	.059	.127	36	.150	.010	.170
3	20	42/36	.010	.057	.123	36	.146	.010	.166
3	18	7x59/44	.010	.070	.151	36	.174	.010	.194
3	18	7x24/40	.010	.070	.151	36	.174	.010	.194
4	34	16/46	.010	.027	.065	44	.074	.010	.094
4	34	10/44	.010	.027	.065	44	.074	.010	.094
4	34	5/40	.010	.028	.067	44	.076	.010	.096
4	32	26/46	.010	.029	.070	44	.079	.010	.099
4	32	16/44	.010	.029	.070	44	.079	.010	.099
4	32	7/40	.010	.029	.070	44	.079	.010	.099

Our standard colors for primary and overall jackets include: white, black, red, green, yellow, blue, brown, orange, gray and violet. Custom color and/or exact color match available; please contact our design team for your specific requirement.

*All measurements are in inches unless otherwise stated.*

[www.newenglandwire.com](http://www.newenglandwire.com)  
Tel: 603.838.6624